

KEY FEATURES

- Fiberglass-Reinforced Pebble-Grain Panel
- Aluminum-Reinforced Perimeter Stiles and Rails
- Mitered Corner Joints Secured By Angled Blocks
- Thermally-Insulated Urethane Core Material
- UL-Certified Fire-Rated Door Frame

MAJOR BENEFITS

Exceptional Durability:

Withstands heavy traffic, abuse and vandalism as well as harsh environmental conditions with ease.

Low Maintenance:

Scratch and stain-resistant pebble-grain exterior looks great for years, requiring only soap and water to clean.

Application-Specific:

An informed choice for challenging environments such as public buildings and service entrances that are prone to damage.



Overcome Harsh Environments Everline Doors



General Specifications

Custom Sizes	Up to 80" (2032 mm) x 216" (5486 mm)
Face Sheets	Resistant to dents, scratches, scuffs, paint, ink and fading.
Foam	5 lbs per cubic foot density.
Stiles and Rails	Configured for maximum strength.
Urethane Core	Ensures impact resistance, flexural strength and thermal insulation.
Thickness	1 ³ / ₄ " (44.5 mm) thick

Colors & Finishes



■ Vision Panel and Louver Options

Factory installed vision panels and louvers ensure proper glazing materials are used to conform with fire and safety building codes.



Vision Panel 10" x 10" 254 x 254 mm



Vision Panel 3" x 33" 76 2 x 838 mm




Vision Panel 24" x 30" 610 x 762 mm



Louvre Panel 12" x 12" 305 x 305 mm



Vision Panel 5" x 20" 127 x 508 mm



Louvre Panel 24" x 24" 610 x 610 mm

Overcome Harsh Environments Everline Doors